

- MANTEMINIENTO FÁCIL
- CONTROL PRE-INSTALADOS
- SERPENTÍN DE ALTA EFICIENCIA
- REMPLAZABLE PISTÓN ADECUADO PARA R410A/R22



FAN COIL



Cableado
(Estandar)


Velocidad de Ventilador



R410a



Ventilador Centrífugo



Filtro Lavable



Model (Duct Indoor Unit)			FC-24CP	FC-36CP	FC-48CP	FC-60CP
Power supply			V/Ph/Hz	220/1/60	220/1/60	220/1/60
Cooling	Capacity	Btu/h	24000	36000	48000	55000
	Capacity	W	7034	10551	14068	16120
	Input	W	3430	3620	6519	7250
	EER	Btu/h.W	7,00	9,94	7,36	7,59
	EER	W/W	2,05	2,91	2,16	2,22
	MCA	A	2,00	2,00	3,00	3,00
MOP			A	3,00	5,00	6,00
MAX. Input consumption			W	210	260	370
Indoor external static pressure			pa	30	30	30
Starting current			A	42	50	80
Operation Control			\	wired	wired	wired
Indoor coil	Number of rows		3	3	3	3
	Tube pitch(a)xrow pitch(b)	mm	22x19.05	22x19.05	22x19.05	22x19.05
	Fin spacing	mm	1,7	1,7	1,7	1,7
	Fin type		Hydrophilic	Hydrophilic	Hydrophilic	Hydrophilic
	Tube outside dia. and type	mm	Φ7.94 inner grooved	Φ7.94 inner grooved	Φ7.94 inner grooved	Φ7.94 inner grooved
	Number of circuits		6	6	6	6
Indoor air flow(High speed)			m³/h	1150	1300	2000
Static Pressure			Pa	30	30	30
Indoor noise level			dB(A)	40~52	45~50	51~56
Indoor unit	Dimension(W*H*D)	Body(mm)	1209x260x680	1209x260x680	1445x260x680	1445x260x680
	Packing(W*H*D)	Body(mm)	1255x325x720	1255x325x720	1490x325x720	1490x325x720
	Net/Gross weight	Body(Kg)	32/36	32/36	46/50	46/50
	Model		YSK110-90F-4P2H105-1	YSK120-150F-4P2H105	YDK110-75F-4P2H105L-1+YSK120-150F-4P2H105-1	YDK110-75F-4P2H105L-1+YSK120-150F-4P2H105-1
Indoor fan motor	Input	W	200	330	165+330	165+330
	Output	W	90	150	75+150	75+150
	Capacitor	uF	5	6	3+6	3+6
	Speed(hi/mi/lo)	r/min	1600/1000/900/870	1300/1150/1080/1030	1380/1300/1200/1130+1360 290/1200/1100	1380/1300/1200/1130+1360/1 290/1200/1100
Max pressure			MPa	4,0	4,0	4,5
Refrigerant type				R410A	R410A	R410A
Refrigerant piping Liquid side/Gas side			mm	Φ9.52/Φ15.88	Φ9.52/Φ19.05	Φ9.52/Φ19.05
Power wiring			mm²	3x1.0	3x1.0	3x1.0
Operation temp			°C	16~32	16~32	16~32
Ambient temp			°C	-7~43	-7~43	-7~43
Application area			m²	28-50	40-70	55-95
Stuffing Quantity(20'/40'/40'HQ)			set	90/168/162	75/168/180	75/168/180

- Las especificaciones están sujetas a cambios sin previo aviso.
- Los números de modelo, imágenes y especificaciones de todos los productos están sujetos a cambios sin previo aviso.

Distribuido por:



PERFECTO PARA



OFICINA



HOTEL



RESTAURANTE